



# DECLARATION OF PERFORMANCE

Nr 13/PP/RN/CE4

We hereby confirm that building product: PINE PLYWOOD

According to: EN636-2G

Thickness: 6mm, 9mm, 12mm, 15mm, 18mm, 20mm, 22mm, 24mm,

Assumed to be used for: INTERNAL USE AS NON-STRUCTURAL COMPONENTS HUMID CONDITIONS

## PRODUCED AND SUPPLIED:

**NOME DA EMPRESA: MADEPLAC COMPENSADOS EIREI**

**CNPJ: 30.595.396/0001-28**

**Address: RUA EMMA DIEDRICHS HORST, 28, JD HORIZONTE, IMBITUVA, PR, BRAZIL**

**CEP 84430-000**

**Telephone: 55 42 3436-1115**

Evaluated and checked for constancy of performance of construction product in accordance with: AVCP SYSTEM 4 EN 13986 – 2004

## ESSENCIAL CHARACTERISTICS

	Declared performance	Technical Specification
Release of Formaldehyde	E1 (phenolic resin bonded)	EN 13986 Annex B Note
Bond Quality	Class 2	EN 314-1/2 Type testing
Density	560 kg/m <sup>3</sup>	EN 323 Type testing

### Dimensional Tolerances:

	Declared performance	Technical Specification
Length and width	+ 0 / -3.0mm	EN 324-2
Squareness	+/-1.0 mm/m	EN 324-2
Straightness	+/-1.0 mm/m	EN 324-2

### Thickness:

	6mm	9mm	12mm	15mm	18mm	20mm	22mm	24mm	25mm	27mm	30mm
Maximum (mm)	6,30	9,50	12,60	15,80	18,90	21	23,10	25,20	26,30	28,40	31,50
Minimum (mm)	5,70	8,50	11,40	14,20	17,10	19	20,90	22,80	23,80	25,60	28,50

30.595.396/0001-28

**MADEPLAC  
COMPENSADOS EIRELI**

Rua Emma Diedrichs Horst, 20  
Jardim Horizonte

84.430-000 - IMBITUVA - PR

Paulo Alexandre Kertscher  
Administrative Manager

Imbituva, 14 fevereiro de 2022.