

Technical Data Sheet

MitrePen

Product Description

MitrePen is quick and clean way to apply MitreBond Activator.

Benefits

- Precision marker rather than a spray.
- Prevents the staining caused by overspray.
- Not classified as hazardous for transport.
- MitrePen covers the same area as 3 x 200ml activator sprays.
- Cures MitreBond in 10 seconds.

Applications

Rapid bonding of substrates using MitreBond.

Directions of Use

- Ensure both surfaces to be joined are clean cut and free from oil or grease.
- Apply MitreBond adhesive (or any other superglue) to one side of the joint.
- Apply MitrePen activator to the other side of the joint.
- Quickly bring the two sides into line and firmly press together, hold for 10 seconds.

Surface Preparations and Finishing

 Application temperature +5°C to +30°C (environment and substrate).

Appearance

 Colourless to pale amber liquid – once applied to surface.

Packaging

- 1 x 50g Adhesive + MitrePen
- 3 x 50g Adhesive + MitrePen

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf-life till 24 months after production date, stored in a dry place.

Health & Safety

Keep in a cool well-ventilated area away from sources of ignition.

Keep away from children at all times.

Keep containers sealed.

Use in a well-ventilated area.

Avoid contact with skin and eyes

For further information, please read the product SDS.

Note: The data, information and values contained in this Technical Data Sheet have been obtained by conducting various tests in a controlled laboratory environment, and should be used for guidance purposes only. Although we believe them to be reliable and accurate, users should always conduct their own tests in their specific working conditions to ensure that the product is suitable and effective for use. It is the user's sole responsibility to determine the suitability of the product for the application. Unika Color Products Ltd. Cannot be held responsible for the results of procedures undertaken elsewhere, nor for the safeguarding of personnel or property, all of which is the duty of the user. Suitability of products or methods is discretionary. Therefore, warrantees or implied usage obligations should not be attributed to and are not the responsibility of Unika Color Products Ltd. Unika Color Products Ltd. are not liable for any financial loss or other damages incurred by the user as a result of the use of this product.